

UNITED STATES PATENT APPLICATION

of

Aaron Schapper

Christian M. Olsen

and

Chadwick L. Wilson

for

ADJUSTABLE SPRAY PATTERN SPRINKLER

1 **ADJUSTABLE SPRAY PATTERN SPRINKLER**

2 **BACKGROUND OF THE INVENTION**

3 **1. Field of the Invention**

4 The present invention relates to systems and methods for irrigating soil. More
5 specifically, the present invention relates to a sprinkler head and related methods that
6 distribute water over a variable spray pattern.

7 **2. Description of Related Art**

8 Irrigation not only permits foodstuffs to be grown, but also enables the cultivation
9 of attractive plant life that otherwise would not have sufficient water to thrive. Many
10 households now utilize sprinkler systems to provide irrigation in a comparatively uniform
11 and trouble-free manner.

12 Often, a control unit such as a timer is used to regularly initiate operation of the
13 sprinkler system to automatically provide the desired distribution of irrigation water. The
14 timer is electrically connected to a plurality of electrically operated valves, each of which
15 is able to permit water to flow into a corresponding zone of the sprinkler system. Each
16 zone may have a number of sprinklers, each of which is designed to distribute water in a
17 predetermined pattern.

18 Sprinklers are available in a wide variety of different configurations, depending
19 on the shape of the area to be irrigated. Some sprinklers spray water in a circular or part-
20 circular pattern. For example, some sprinklers are designed to provide a quarter-circle
21 pattern, while others spray water in half circle, three-quarters circle, or full-circle
22 patterns. Additionally, some sprinklers are designed to irrigate a strip between a
23 sidewalk and a street. Such sprinklers typically distribute water within a generally

1 rectangular area. Strip sprinklers include multiple types, including center strip sprinklers,
2 side strip sprinklers, and end strip sprinklers, depending on where the sprinkler is to be
3 positioned within the strip.

4 A typical irrigation system includes a variety of sprinkler types, including several
5 of the above. Consequently, the installer must have a relatively wide inventory of
6 sprinklers available. The installer must carefully lay out the irrigation system prior to
7 purchasing the components to obtain the correct quantity of each sprinkler type. A
8 change in irrigation plans may necessitate additional trips to the store to purchase and/or
9 exchange sprinklers. Some areas, such as those with corners between 90°, 180°, 270°,
10 and 360°, are difficult or impossible to adequately or efficiently irrigate with the limited
11 number of spray angles available. Furthermore, if the irrigation needs within a certain
12 area change over time, one or more sprinklers may need to be replaced with different
13 types.

14 In order to alleviate some of the foregoing problems, variable arc sprinklers have
15 been developed. Many known variable arc sprinklers have two helical edges that define a
16 slot. The angular width of the slot can be varied by rotating one helical edge with respect
17 to the other to vary the magnitude of the angle within which water is sprayed from the
18 sprinkler.

19 Unfortunately, known variable arc sprinklers have a number of inherent
20 limitations. For example, many such sprinklers require axial (*i.e.*, vertical) motion of the
21 top end of the sprinkler to provide adjustment. Hence, even if the sprinkler is initially
22 installed at the proper height, subsequent adjustment of the sprinkler may remove the top
23 of the sprinkler from its initial position. Thus, the sprinkler may not have sufficient spray
24 clearance, or may be damaged by lawn care equipment.

1 Furthermore, many known variable arc sprinklers are unable to provide an even
2 distribution of water across the selected angle. Thus, the corresponding soil is unevenly
3 irrigated. Many known variable arc sprinklers are unable to effectively provide full-
4 circle coverage because the flow of water from the sprinkler head is discontinuous over
5 the adjacent ends of the arc. Hence, even at a “full-circle” setting, there may be 5% or
6 more along which water is not sprayed from the head, or is sprayed at such a low volume
7 that corresponding region is not sufficiently irrigated.

8 Yet further, many known variable arc sprinklers are relatively complex, and are
9 therefore far more expensive than their fixed-angle counterparts. Some known variable
10 arc sprinklers have parts with relatively complex geometries that cannot be readily
11 produced through the use of economical methods. Some adjustable sprinklers also have
12 visible parts that are asymmetrical, and therefore may not look attractive to a user.

13 Still further, known variable arc sprinklers are generally not suitable for strip
14 irrigation because they broadcast water over a pie-shaped or circular area that does not
15 suit the dimensions of typical strips. Accordingly, the problems described above have
16 not been fully remedied by existing sprinkler designs.

17 18 SUMMARY OF THE INVENTION

19 The apparatus of the present invention has been developed in response to the
20 present state of the art, and in particular, in response to the problems and needs in the art
21 that have not yet been fully solved by currently available irrigation systems and
22 components. Thus, it is an overall objective of the present invention to provide irrigation
23 systems and sprinklers that remedy the shortcomings of the prior art.

1 To achieve the foregoing objective, and in accordance with the invention as
2 embodied and broadly described herein in the preferred embodiment, an irrigation system
3 is used to irrigate an area. The irrigation system has a valving system designed to control
4 flows of an irrigation liquid, such as water, to a plurality of water distribution units such
5 as sprinklers. The sprinklers receive water from a plurality of distribution conduits, each
6 of which is in communication with a valve assembly. Each valve assembly has a fluid
7 transfer portion and an actuator portion designed to actuate elements within the valve
8 housing to move the valve assembly between an open configuration and a closed
9 configuration.

10 Each valve assembly also has a pair of wires that conveys a valve activation
11 signal to the actuator to move the valve assembly between the open and closed
12 configurations. The valve assemblies may be connected to a feeder conduit to form a
13 manifold that receives water from a main line. The manifold may be disposed
14 underground, within a manifold box covered by a lid. Alternatively, the manifold may be
15 attached to an above-ground spigot for use in a hose bib irrigation system. Control unit
16 wires extend from the valve wires to a control unit, such as a timer.

17 At least one of the sprinklers may be a pop-up type sprinkler, and may thus have a
18 casing and a pop-up stem designed to slide upward from the casing during operation of
19 the sprinkler. The pop-up stem supports a spray head from which the water is ejected.
20 The spray head is designed to spray water through a variable arc selectable by a user.

21 The spray head may have an adjustment dial, a shaft, a deflector, a housing, a
22 cam, and an adjustment screw. A filter is inserted into the pop-up stem to rest underneath
23 the spray head. The housing has an inlet portion adjacent to the end of the pop-up stem
24 and an outlet portion disposed above (*i.e.*, downstream of) the inlet portion. The housing

1 has an outer wall with a generally tubular shape through which water flows. The housing
2 is centered about a cam axis. Threads are formed on the inside surface of the outer wall
3 to permit threaded engagement of the inlet portion with the pop-up stem. The outer wall
4 has a plurality of indentations disposed on the outer surface of the inlet portion to
5 facilitate rotation of the housing by hand so that the spray head can easily be manually
6 attached to or removed from the pop-up stem.

7 The outlet portion has a plate that crosses the interior of the housing. A central
8 hole and a receiving hole are formed in the plate. The plate has a plurality of outlet
9 apertures, each of which extends through an angle and has a gradually increasing radius
10 within the angle, with respect to the cam axis. The outlet apertures are arranged end-to-
11 end to form a spiral shape extending full-circle.

12 The deflector is attached to the housing and is disposed directly above the housing
13 to distribute water exiting the outlet apertures. The deflector has a lip that extends
14 outward from the cam axis, and is radially coextensive with the outer wall of the housing.
15 The deflector also has a central hole extending along the cam axis and a conical portion
16 that extends from the lip toward the housing. A skirt extends from the conical portion
17 toward the housing. The skirt has a spiral shape similar to that of the combined outlet
18 apertures. The skirt is sized such that its spiral shape is aligned with the interior edges of
19 the outlet apertures. A hub and an orientation post extend downward from the skirt to
20 seat in the central hole and the receiving hole, respectively.

21 The cam has an outer edge that also has a spiral shape. The outer edge is also
22 sized to align with the interior edges of the outlet apertures, or is sized only slightly larger
23 than the shape defined by the interior surfaces. The cam also has a central hole coaxial
24 with the cam axis. The adjustment dial has an outer edge that is textured to facilitate

1 gripping by hand and a central hole coaxial with the cam axis. The shaft has a first end, a
2 second end, and a bore with a threaded interior surface. The adjustment screw has a head
3 coupled to a shaft on which corresponding threads are disposed. The shaft terminates in a
4 slot.

5 The adjustment dial, shaft, deflector, housing, cam, and adjustment screw may be
6 easily manufactured through the use of known methods. According to one example, the
7 housing and the deflector may be made of plastic via injection molding. The shaft may
8 be cut from a stock length of interior threaded, tubular metal or plastic. The adjustment
9 dial and the cam may be stamped from metal or plastic sheets. The adjustment screw
10 may be formed via casting or other known methods.

11 The adjustment dial, shaft, deflector, housing, cam, and adjustment screw are
12 assembled as follows. The housing is disposed such that the hub and the orientation post
13 are aligned with the central hole and the receiving hole, respectively, of the plate. The
14 housing and the deflector are then moved together so that the hub is inserted into the
15 central hole and the orientation post is inserted into the receiving hole. The housing and
16 the deflector may or may not be attached together. The engagement of the orientation
17 post with the receiving hole keeps the deflector from rotating with respect to the housing.

18 The first end of the shaft is then pressed into the central hole of the adjustment
19 dial and the shaft is inserted through the central holes of the deflector and the housing so
20 that the adjustment dial is disposed adjacent to the deflector. The cam is pressed onto the
21 exposed second end of the shaft in such a manner that the second end is inserted into the
22 central hole of the cam. The adjustment screw is then rotated into engagement with the
23 threads of the bore of the shaft in such a manner that the slot is exposed proximate the
24 first end of the shaft and the head extends from the second end. The filter is inserted into

1 the pop-up stem, which has already been assembled with the casing, and the housing is
2 threaded into engagement with the pop-up stem to complete assembly of the sprinkler.

3 In operation, water moves upward through the pop-up stem and flows through the
4 filter. The water flows through the annular gap between the head of the adjustment screw
5 and a tapered bore of the filter. The position of the head with respect to the tapered bore
6 determines the flow rate of water through the sprinkler. After leaving the filter, the water
7 flows into the inlet portion of the housing and against the cam. The water then flows
8 through the portion of the outlet apertures that is not covered by the cam. After leaving
9 the outlet apertures, the water flows against the conical portion of the deflector and is
10 deflected away from the cam axis to spray outward from the spray head.

11 The adjustment dial may be rotated to rotate the shaft, thereby rotating the cam.
12 The relative sizes of the cam and the outlet apertures enable the orientation of the cam to
13 determine the angle through which water flows through the outlet apertures. The
14 adjustment dial may be rotated to permit water to flow from the spray head through an
15 arc angle ranging from about 20° to about 360° (full-circle). The adjustment screw may
16 be rotated to move the head of the adjustment screw closer to or further from the tapered
17 bore, thereby controlling the quantity of water distributed by the spray head.

18 According to one alternative embodiment of the invention, the adjustment dial,
19 shaft, cam, and adjustment screw are substantially as described above. As above, the
20 housing also has outlet apertures disposed in a spiral shape. However, the deflector and
21 housing are designed such that the deflector is able to rotate with respect to the housing.
22 The deflector has a lip from which a conical portion extends toward the housing. The
23 conical portion is truncated, and a plurality of vanes is formed on the resulting surface.

1 The plate of the housing has no receiving hole, and the deflector has no orientation post;
2 accordingly, relative rotation between the housing and the deflector is permitted.

3 The vanes are curved in such a manner that water flowing from the outlet
4 apertures impinges against the vanes and causes the deflector to rotate. The water moves
5 through the grooves between the vanes and exits the grooves with tangential, as well as
6 radial, velocity. The rotation of the deflector may provide more even water distribution
7 and attractive operation.

8 According to another alternative embodiment of the invention, a spray head may
9 be designed to provide variable strip irrigation. Such a spray head may have an
10 adjustment dial, a shaft, and an adjustment screw similar to those of the previous
11 embodiments. A housing, a deflector, and a cam are also provided. Like those of the
12 previous embodiments, the housing has an inlet portion and an outlet portion that
13 includes a plate in which a plurality of outlet apertures are formed. However, the outlet
14 apertures do not form a spiral; rather, the outlet apertures are circular or elongated along a
15 straight path.

16 Like the deflector of the first embodiment, the deflector includes a lip from which
17 a conical portion extends toward the housing. A hub and an orientation post extend from
18 the conical portion toward the housing. The plate of the housing has a central hole and a
19 receiving hole that receive the hub and the orientation post in a manner that prevents
20 relative rotation between the deflector and the housing.

21 A plurality of water distribution features, such as specially shaped grooves, is
22 formed in the conical portion. Each of the water distribution features is aligned with one
23 of the outlet apertures to distribute water from the corresponding outlet aperture. The
24 water distribution features include multiple configurations that are designed to provide a

1 plurality of different spray patterns such as center strip irrigation, side strip irrigation, and
2 end strip irrigation.

3 The cam also is not spiral-shaped, but has a generally circular outer edge with a
4 notch extending inward. The cam has a central hole and a hole disposed on the opposite
5 side of the central hole from the notch. The cam is coupled to the adjustment dial in a
6 manner similar to those of the previous embodiments. Rotation of the adjustment dial
7 rotates the cam to determine which of the outlet apertures will be uncovered by the cam
8 to permit water to flow to the corresponding water distribution feature.

9 The hole and the notch cooperate such that, in one orientation of the cam, water is
10 able to flow simultaneously through two of the outlet apertures to reach two of the water
11 distribution features, thereby providing center strip irrigation. In another orientation,
12 flow may be permitted only to one of the water distribution features used for center strip
13 irrigation to provide end strip irrigation. In another orientation, flow may be permitted to
14 a different water distribution feature to provide side strip irrigation.

15 Through the use of the apparatus and method of the invention, a sprinkler may
16 provide relatively uniform water distribution over a continuously variable angle including
17 a full-circle spray pattern. A sprinkler may alternatively be adjustable between different
18 strip irrigation settings including center strip irrigation, side strip irrigation, and end strip
19 irrigation. Furthermore, such sprinklers may be easy to use and may be produced at
20 relatively low cost. These and other features and advantages of the present invention will
21 become more fully apparent from the following description and appended claims, or may
22 be learned by the practice of the invention as set forth hereinafter.

1 **BRIEF DESCRIPTION OF THE DRAWINGS**

2 A particular description of the invention will be rendered by reference to specific
3 embodiments thereof which are illustrated in the appended drawings. Understanding that
4 these drawings depict only typical embodiments of the invention and are not therefore to
5 be considered to be limiting of its scope, the invention will be described and explained
6 with additional specificity and detail through the use of the accompanying drawings in
7 which:

8 Figure 1 is a perspective view of an irrigation system according to one
9 embodiment of the invention;

10 Figure 2 is an exploded, perspective view of a spray head of one of the sprinklers
11 of the irrigation system of Figure 1;

12 Figure 3A is a plan view of the housing and the cam of the spray head of Figure 2,
13 with the housing and cam (shown in phantom lines) relatively positioned for 90°
14 watering;

15 Figure 3B is a plan view of the housing and the cam of the spray head of Figure 2,
16 with the housing and cam (shown in phantom lines) relatively positioned for 180°
17 watering;

18 Figure 3C is a plan view of the housing and the cam of the spray head of Figure 2,
19 with the housing and cam (shown in phantom lines) relatively positioned for full-circle
20 watering;

21 Figure 4 is an exploded, perspective view of a spray head of a sprinkler according
22 to one alternative embodiment of the invention;

23 Figure 5 is bottom view of the deflector of the spray head of Figure 4;

1 Figure 6 is an exploded, perspective view of a spray head of a sprinkler according
2 to one alternative embodiment of the invention;

3 Figure 7A is a plan view of the housing and the cam of the spray head of Figure 6,
4 with the housing and cam (shown in phantom lines) relatively positioned for center strip
5 irrigation;

6 Figure 7B is a plan view of a strip area in which the spray head of Figure 6 is
7 installed to provide center strip irrigation;

8 Figure 7C is a plan view of the housing and the cam of the spray head of Figure 6,
9 with the housing and cam (shown in phantom lines) relatively positioned for side strip
10 irrigation;

11 Figure 7D is a plan view of a strip area in which the spray head of Figure 6 is
12 installed to provide side strip irrigation;

13 Figure 7E is a plan view of the housing and the cam of the spray head of Figure 6,
14 with the housing and cam (shown in phantom lines) relatively positioned for side strip
15 irrigation; and

16 Figure 7F is a plan view of a strip area in which the spray head of Figure 6 is
17 installed to provide end strip irrigation.

18
19 **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

20 The presently preferred embodiments of the present invention will be best
21 understood by reference to the drawings, wherein like parts are designated by like
22 numerals throughout. It will be readily understood that the components of the present
23 invention, as generally described and illustrated in the figures herein, could be arranged
24 and designed in a wide variety of different configurations. Thus, the following more

1 detailed description of the embodiments of the apparatus, system, and method of the
2 present invention, as represented in Figures 1 through 7F, is not intended to limit the
3 scope of the invention, as claimed, but is merely representative of presently preferred
4 embodiments of the invention.

5 For this application, the phrases “connected to,” “coupled to,” and “in
6 communication with” refer to any form of interaction between two or more entities,
7 including mechanical, electrical, magnetic, electromagnetic, and thermal interaction. The
8 phrase “attached to” refers to a form of mechanical coupling that restricts relative
9 translation or rotation between the attached objects. The phrases “pivotally attached to”
10 and “slidably attached to” refer to forms of mechanical coupling that permit relative
11 rotation or relative translation, respectively, while restricting other relative motion.

12 The phrase “attached directly to” refers to a form of attachment by which the
13 attached items are either in direct contact, or are only separated by a single fastener,
14 adhesive, or other attachment mechanism. The term “abutting” refers to items that are in
15 direct physical contact with each other, although the items may not be attached together.
16 The terms “integrally formed” refer to a body that is manufactured integrally, *i.e.*, as a
17 single piece, without requiring the assembly of multiple pieces. Multiple parts may be
18 integrally formed with each other if they are formed from a single workpiece.

19 Referring to Figure 1, a perspective view depicts an irrigation system 10
20 according to one embodiment of the invention. The irrigation system 10 has a
21 longitudinal direction 12, a lateral direction 14, and a transverse direction 16. The
22 irrigation system 10 incorporates a valving system 20, which will be described in greater
23 detail subsequently.

1 The irrigation system 10 is designed to receive water 22 via a main line 24. In
2 this application, “water” includes not only pure water, but also water with additives such
3 as fertilizers, pesticides, or the like. The water 22 is distributed by a plurality of water
4 distribution units over a patch of land designated for plant growth.

5 “Water distribution unit” encompasses a variety of devices used to spread water,
6 such as pop-up sprinkler heads, rotary sprinklers, bubblers, drip irrigation systems, and
7 the like. The irrigation system 10 includes water distribution units in the form of a first
8 sprinkler 26, a second sprinkler 28, and a third sprinkler 30. The sprinklers 26, 28, 30 are
9 arrayed to irrigate an area 32. Of course, an irrigation system 10 may have more or less
10 than three sprinklers. In Figure 1, each of the sprinklers 26, 28, 30 is a pop-up sprinkler
11 that includes a casing 33, a pop-up stem 34 designed to extend upward from within the
12 casing 32 in response to water pressure, and a spray head 35 disposed on the top end of
13 the corresponding pop-up stem 34 to distribute the water 22.

14 The first, second and third sprinklers 26, 28, 30 are supplied with water by first,
15 second and third distribution conduits 36, 38, 40, respectively. Each of the distribution
16 conduits 36, 38, 40 may extend further to supply additional water distribution units (not
17 shown). In this application, a “conduit” is any structure capable of conducting a fluid
18 under pressure from one location to another.

19 Water flow to the first, second, and third distribution conduits 36, 38, 40 is
20 controlled by a first valve assembly 46, a second valve assembly 48, and a third valve
21 assembly 50, respectively. The valve assemblies 46, 48, 50 may optionally operate to
22 permit water flow to only one of the conduits 36, 38, 40 at any given time, so that each
23 conduit 36, 38, 40, in turn, receives the full pressure and flow rate of water from the main

1 line 24. The first, second, and third valve assemblies 46, 48, 50 have a first valve 52, a
2 second valve 54, and a third valve 56, respectively.

3 As depicted in Figure 1, the first valve assembly 46 is in the open configuration to
4 supply water to the first sprinkler 26 via the first conduit 36. Hence, the pop-up stem 34
5 of the first valve assembly 46 is extended upward from the corresponding casing 33, and
6 the spray head 35 of the first sprinkler 26 is exposed to permit water flow from the spray
7 head 35. The second and third valve assemblies 48, 50 are in the closed configuration so
8 that no significant amount of water flows into the second and third conduits 38, 40, and
9 the second and third sprinklers 28, 30 are inactive. The pop-up stems 34 and spray heads
10 35 of the second and third sprinklers 28, 30 are retracted into the corresponding casings
11 32.

12 Each of the valves 52, 54, 56 has a fluid transfer portion 60 in fluid
13 communication with the associated distribution conduit 36, 38, or 40. The fluid transfer
14 portion 60 contains one or more elements that block or unblock water flow through the
15 fluid transfer portion 60. Thus, each of the valves 52, 54, 56 has a closed configuration,
16 in which water flow is blocked, and an open configuration, in which water flow is
17 comparatively freely permitted.

18 Each of the valve assemblies 46, 48, 50 also has an actuator portion 62 attached to
19 the fluid transfer portion 60. The actuator portion 62 moves the interior elements of the
20 fluid transfer portion 60 to move the valve assembly 46, 48, 50 between the open and
21 closed configurations. The actuator portion 62 may include an electrically operated
22 device such as a linear or rotary solenoid, piezoelectric actuator, or electric motor. The
23 valve assemblies 46, 48, 50 also include first valve wires 66, second valve wires 68, and

1 third valve wires 70, respectively. Each set of valve wires 66, 68, 70 is coupled to the
2 actuator portion 62 of the corresponding valve 52, 54, 56.

3 In this application, the term “valve” generally refers to the combination of the
4 fluid transfer portion 60 and the actuator portion 62. The term “valve” is not limited to
5 the embodiment shown, but may include a wide variety of actuator and fluid transfer
6 portion combinations.

7 The valve assemblies 46, 48, 50 are interconnected to form a manifold 72, to
8 which the main line 24 and the distribution conduits 36, 38, 40 are attached. More
9 precisely, the manifold 72 includes a feeder conduit 74 that receives water from the main
10 line 24 at one end. The valve assemblies 46, 48, 50 are arranged generally perpendicular
11 to the feeder conduit 74 to receive the water. The manifold 72 is disposed within a
12 manifold box 82, which may be disposed generally underground, as depicted. The
13 manifold box 82 has a lid 84 designed to provide access to the manifold 72 for repairs or
14 maintenance.

15 A plurality of control unit wires 86 are connected to valve wires 66, 68, 70.
16 Except at the ends, the control unit wires 86 are covered by a sheath 88 designed to
17 gather and protect the control wires 86. The control unit wires 86 extend from the valve
18 wires 66, 68, 70 to a control unit designed to transmit valve activation signals through the
19 control wires 86. As depicted, the valve wires 66, 68, 70 are connected to the control unit
20 wires 86 via conventional wire nuts. If desired, the control wires 86 may alternatively be
21 coupled to the valve wires 66, 68, 70 via some type of electrical junction unit.

22 The control unit may take the form of a timer 90, as illustrated in Figure 1. The
23 timer 90 transmits the valve activation signals via the control unit wires 86 according to a
24 schedule established by a user. The phrase “control unit” is not limited to a timer, but

1 may include any other device that transmits a valve activation signal. Such devices
2 include simple switches, remote receivers, control system processors designed to measure
3 variables and control operation of the irrigation system 10 based on those variables, and
4 the like. The timer 90 may be attached to a wall 92 near the manifold box 82, as shown,
5 or may be disposed at a remote location.

6 The configuration of Figure 1 is not the only application in which valves
7 according to the invention may be used. Valves such as the valves 52, 54, 56 may be
8 used in other types of irrigation systems. For example, the valves 52, 54, 56 may be
9 incorporated into a hose bib system. Thus, the valves 52, 54, 56 may be attached to a
10 common above-ground garden spigot, either individually or as part of a differently
11 configured manifold. The distribution conduits 36, 38, 40 may be effectively replaced
12 with hoses or other above-ground irrigation water lines. One or more timers may be
13 incorporated into the housings of the valves 52, 54, 56 to provide a simple and compact
14 irrigation control system.

15 Referring to Figure 2, an exploded, perspective view illustrates the spray head 35
16 of one of the sprinklers 26, 28, 30 of Figure 1 in greater detail. As shown, the spray head
17 35 includes an adjustment dial 100, a shaft 102, a deflector 104, a housing 106, a cam
18 108 and an adjustment screw 110. The adjustment dial 100, shaft 102, deflector 104,
19 housing 106, cam 108, and adjustment screw 110 are assembled together to form the
20 spray head 35, which threadably engages the top portion of the corresponding pop-up
21 stem 34. A filter 112 is inserted into the pop-up stem 34 below the spray head 35 to filter
22 water entering the spray head 35 and to provide flow rate adjustment in a manner that
23 will be described subsequently.

1 As shown, the housing 106 has an inlet portion 114 and an outlet portion 116.
2 The housing 106 has an outer wall 118 with a generally tubular shape concentric with a
3 cam axis 120. The outer wall 118 has female threads disposed on an interior surface (not
4 shown) of the inlet portion 114. The outer wall 118 also has indentations 122 distributed
5 about its outer surface, within the inlet portion 114 to facilitate rotation of the housing
6 106 by hand. More precisely, a user may grip the outer wall 118 with a thumb and
7 forefinger and rotate the housing 106 via the indentations 122 with the thumb and
8 forefinger to rotate the spray head 35 into engagement with the pop-up stem 34.

9 The outlet portion 116 of the housing 106 has a plate 124 with a substantially flat
10 configuration that extends across the open interior of the outer wall 118, substantially
11 perpendicular to the cam axis 120. In this application, “substantially flat” refers to an
12 element with a face extending substantially along a plane. A “plate” is a substantially flat
13 element with a comparatively small thickness perpendicular to the face. A central hole
14 126 is formed in the plate 124. The central hole 126 has a lip 128 that steps inward so
15 that the central hole 126 has two distinct diameters. The plate 124 also has a receiving
16 hole 130 that does not extend entirely through the plate 124.

17 Additionally, the plate 124 has a plurality of outlet apertures, including a first
18 outlet aperture 132, a second outlet aperture 134, a third outlet aperture 136, a fourth
19 outlet aperture 138, a fifth outlet aperture 140, and an sixth outlet aperture 142. As
20 shown, each of the outlet apertures 132, 134, 136, 138, 140, 142 is elongated along a
21 curved path with a radius that gradually increases within an angle, with respect to the cam
22 axis 120.

23 More precisely, as each of the outlet apertures 132, 134, 136, 138, 140, 142
24 extends clockwise (as viewed from above), with respect to the cam axis 120, the radius of

1 each outlet aperture 132, 134, 136, 138, 140, 142 increases with respect to the cam axis
2 120. The outlet apertures 132, 134, 136 138, 140, 142 are disposed end-to-end so that,
3 collectively, the outlet apertures 132, 134, 136, 138, 140, 142 follow a path that extends
4 full-circle (*i.e.*, about a substantially circular pattern) about the cam axis 120, with a
5 radius that gradually increases throughout the 360° angle of rotation of the path.

6 The outlet apertures 132, 134, 136, 138, 140, 142 are separated from each other
7 by bridges 144. In alternative embodiments, the bridges 144 may be omitted to provide
8 one single outlet aperture that provides the entire range of adjustability for a spray head.
9 In the embodiment of Figure 2, the bridges 144 are included as an optional feature to
10 avoid undesired flexure of the portion of the plate 124 that lies within the outlet apertures
11 132, 134, 136, 138, 140, 142. Such flexure may alter the width of the corresponding
12 outlet aperture(s), thereby adversely affecting the consistency of water distribution from
13 the spray head.

14 In the embodiment of Figure 2, the housing 106 is integrally formed. In
15 alternative embodiments, the housing 106 may include multiple parts. For example, the
16 inlet and outlet portions 114, 116 may be separately formed, or the outer wall 118 may be
17 formed separately from the plate 124.

18 The deflector 104 has a lip 150 that has a diameter approximately equal to the
19 outer diameter of the outer wall 118 of the housing 106. A central hole 152 is formed in
20 the deflector 104, concentric with the cam axis 120. The deflector 104 also has a conical
21 portion 154 that extends from the lip 150 toward the housing 106. The conical portion
22 154 is centered on the cam axis 120 and is angled such that water impinging against the
23 conical portion 154 from the housing 106 will generally be directed outward and upward
24 from the cam axis 120. In this application, a “generally conical shape” may include

1 protrusions, curves, or other departures from the conical shape. Also, a truncated cone or
2 frusto-conical shape has a “generally conical shape.”

3 The deflector 104 also has a skirt 156 extending from the conical portion 154
4 toward the housing 106. The skirt 156 has a gradually increasing radius within the same
5 angle through which the outlet apertures 132, 134, 136, 138, 140, 142 collectively extend
6 (*e.g.*, full-circle in the embodiment of Figure 2). The skirt 156 is sized to line up with the
7 interior edges of the outlet apertures 132, 134, 136, 138, 140, 142. Thus, water exiting
8 the outlet apertures 132, 134, 136, 138, 140, 142 is blocked from moving toward the cam
9 axis 120 by the skirt 156, but the skirt 156 does not significantly block water flow out of
10 the outlet apertures 132, 134, 136, 138, 140, 142. The skirt 156 has a flat edge 158
11 aligned with the space between the first and sixth outlet apertures 132, 142.

12 The deflector 104 also has a hub (not visible) and an orientation post (not visible)
13 that extend toward the housing 106 from the skirt 156. The hub and the orientation post
14 are inserted into the central hole 126 and the receiving hole 130, respectively, of the plate
15 124. The engagement of the hub and the central hole 126 and the engagement of the
16 orientation post and the receiving hole 130 keep the deflector 104 from rotating with
17 respect to the housing 106. Thus, during operation of the spray head 35, the skirt 156 is
18 always properly oriented with respect to the outlet apertures 132, 134, 136, 138, 140, 142.

19 The cam 108 has an outer edge 160. Like the skirt 156, the outer edge 160 has a
20 gradually increasing radius within the same angle through which the outlet apertures 132,
21 134, 136, 138, 140, 142 collectively extend (*e.g.*, full-circle in the embodiment of Figure
22 2). The outer edge 160 may also be aligned with the interior edges of the outlet apertures
23 132, 134, 136, 138, 140, 142, or may extend only just past the interior edges of the outlet
24 apertures 132, 134, 136, 138, 140, 142. Thus, the cam 108 may be rotated to a variety of

1 orientations with respect to the outlet apertures 132, 134, 136, 138, 140, 142 to uncover a
2 variable angular portion of the combined outlet apertures 132, 134, 136, 138, 140, 142.
3 The size of the angle that is uncovered determines the size of the angle through which
4 water is sprayed from the spray head 35, as will be explained in greater detail
5 subsequently.

6 The cam 108 also has a central hole 162 coaxial with the cam axis 120. The outer
7 edge 160 has a flat edge 164 aligned with the space between the first and sixth outlet
8 apertures 132, 142. The cam 108 may be constructed of a metal or any other suitable
9 rigid material. Rust resistant metals such as stainless steel, aluminum, copper, brass and
10 the like may be used to reduce the likelihood of corrosion.

11 In alternative embodiments, a cam (not shown) may be uniformly thicker, or may
12 have a domed or conical shape that is thicker about the corresponding central hole to
13 facilitate press fitting with the shaft 102. In other alternative embodiments, a cam may
14 have a generally ring-shaped configuration with a spiral-shaped inside edge. In yet other
15 alternative embodiments, a cam may have a hole pattern that provides variable flow
16 through the outlet apertures 132, 134, 136, 138, 140, 142, in place of a spiral-shaped
17 edge.

18 The adjustment dial 100 may similarly be formed of a rust resistant metal such as
19 stainless steel, aluminum, copper, or brass or any other suitable material. The adjustment
20 dial 100 has an outer edge 170 that extends along a circle. As shown, the outer edge 170
21 may be knurled or otherwise textured to facilitate rotation of the adjustment dial 100 by
22 hand. The adjustment dial 100 also has a central hole 172 that is coaxial with the cam
23 axis 120.

1 The adjustment dial 100 may have a diameter slightly larger than that of the
2 remainder of the spray head 35. Accordingly, when the pop-up stem 34 retracts into the
3 casing 33 after completion of watering, the remaining components of the spray head 35
4 slide into the casing 33, and the edge of the adjustment dial 100 seats against the lip of
5 the opening of the casing 33 from which the pop-up stem 34 emerges. Accordingly, the
6 adjustment dial 100 may be gripped and rotated to adjust the spray pattern of the spray
7 head 35 when the pop-up stem 34 is in the retracted position.

8 In this application, the word “dial” is to be interpreted broadly. For example, in
9 alternative embodiments, an adjustment dial need not be circular in shape, but may have
10 any shape that is easily rotated by a user, with or without tooling. It may even be
11 beneficial to provide an adjustment dial that must be rotated through the use of tooling to
12 help prevent tampering.

13 Like the cam 108 and the adjustment dial 100, the shaft 102 may be formed of a
14 rust resistant metal such as stainless steel, aluminum, copper, or brass or any other
15 suitable material. The shaft 108 serves to couple the adjustment dial 100 to the cam 108
16 in such a manner that rotation of the adjustment dial 100 causes the cam 108 to rotate.
17 More precisely, the shaft 108 has a first end 174 that fits into the central hole 172 of the
18 adjustment dial and a second end 176 that fits into the central hole 162 of the cam 108.
19 The first and second ends 174, 176 may be sized and/or shaped in such a manner that a
20 press fit exists between the first end 174 and the central hole 172 of the adjustment dial
21 100 and a press fit exists between the second end 176 and the central hole 162 of the cam
22 108.

23 The shaft 102 has a bore 178 that is threaded and sized to receive the adjustment
24 screw 110 such that the adjustment screw 110 is able to rotate to move along the

1 transverse direction 16, *e.g.*, upward when the spray head 35 is oriented as in Figure 1.
2 The outside diameter of the shaft 102 is sized such that clearance exists between the shaft
3 102 and the central hole 152 of the deflector 104 and between the shaft 102 and the lip
4 128 of the central hole 126 of the plate 124. Thus, the shaft 102 is able to rotate with
5 respect to the housing 106 and the deflector 104.

6 The adjustment screw 110 has a head 180 disposed adjacent to the filter 112. The
7 head 180 has a domed shape designed to cooperate with the filter 112 to control the rate
8 at which water enters the spray head 34. Additionally, the adjustment screw 110 has a
9 plurality of threads 182 and a slot 184 disposed on the opposite side of the adjustment
10 screw 110 from the head 180.

11 The filter 112 has a lip 186 sized to rest on a corresponding shelf (not shown)
12 within the pop-up stem 34. The filter 112 also has a tapered bore 188 that extends inward
13 from the lip 186. The tapered bore 188 has a funnel-like shape through which water
14 flows to enter the spray head 35. The space between the tapered bore 188 and the head
15 180 of the adjustment screw 110 is the flow path through which water is able to enter the
16 spray head 35. Moving the head 180 with respect to the tapered bore 188 controls the
17 flow rate of water entering the spray head 35, as will be described subsequently. The
18 filter 112 has a mesh 190 through which water must flow to reach the tapered bore 188.
19 The mesh 190 keeps the spray head 35 unclogged by trapping solid matter to keep it from
20 entering the spray head 35.

21 The adjustment dial 100, shaft 102, deflector 104, housing 106, cam 108, and
22 adjustment screw 110 may be manufactured according to a number of methods.
23 According to one method, the adjustment dial 100 and the cam 108 may be stamped from
24 sheets of metal or any other suitable material. As mentioned above, rust-resistant metals

1 such as aluminum, stainless steel, copper, and brass may be used. The shaft 102 may be
2 cut from a length of stock tubular material, which may be formed via known methods.
3 The threads may be present in the stock material, or may be formed via a tapping
4 operation or the like. The adjustment screw may be die cast or otherwise formed of a
5 rust-resistant material like those listed above. The deflector 104 and the housing 106
6 may each be formed of plastic via injection molding or other known methods.

7 The adjustment dial 100, shaft 102, deflector 104, housing 106, cam 108, and
8 adjustment screw 110 may be assembled via a variety of methods. According to one
9 method, the deflector 104 may first be aligned with the housing 106 so that the hub and
10 the orientation post are coaxial with the central hole 126 and the receiving hole 130,
11 respectively, of the plate 124. The deflector 104 and the housing 106 may then be moved
12 toward each other so that the hub and the orientation post are inserted into the central
13 hole 126 and the receiving hole 130, respectively. A press fit may be formed to keep the
14 housing 106 and the deflector 104 together. Alternatively, methods such as RF welding,
15 ultrasonic welding, adhesive bonding, or the like may be used to keep the deflector 104
16 and the housing 106 together.

17 The cam 108 may then be aligned with the shaft 102 and the cam 108 and shaft
18 102 may be moved together so that the second end 176 of the shaft 102 enters the central
19 hole 162 of the cam 108. The second end 176 may be sized to form an interference fit
20 within the central hole 162. Accordingly, some force may be required to insert the
21 second end 176 into the central hole 162. The first end 174 of the shaft 102 may then be
22 inserted through the central hole 126 of the plate 124 and then through the central hole
23 152 of the deflector 104 in such a manner that the cam 108 is disposed in the inlet portion
24 114 of the housing. The plate 124 and the deflector 104 are then disposed between the

1 cam 108 and the first end 174, and the cam 108 is disposed upstream of the plate 124 to
2 block water flow through the outlet apertures 132, 134, 136, 138, 140, 142.

3 The first end 174 of the shaft 102 is then aligned with and inserted into the central
4 hole 172 of the adjustment dial 100 in a manner similar to that of the cam 108. Again,
5 force may be applied to form an interference fit. The cam 108 and/or the adjustment dial
6 100 may be made somewhat thicker, if desired, to provide a greater transverse length of
7 the central holes 162, 172 to provide a more secure press fit. Alternatively, the cam 108
8 and/or the adjustment dial 100 may be made thicker around the central holes 162, 172
9 and may step to a thinner configuration or may be domed or otherwise shaped in such a
10 manner that the outer edges 160, 170 are relatively thinner in the transverse direction 16.
11 If desired, other attachment methods such as welding, adhesive bonding, or the like may
12 be applied in addition to or in the alternative to the press fits described above.

13 The adjustment screw 110 may then be inserted into engagement with the bore
14 178 of the shaft 102. More precisely, the slot 184 of the adjustment screw 110 is inserted
15 into the bore 178 proximate the second end 176 of the shaft 102. The adjustment screw
16 110 is then rotated about the cam axis so that the slot 184 travels through the shaft 102
17 and emerges from the bore 178 at the first end 174.

18 The spray head 35 is then fully assembled and ready for installation on the pop-up
19 stem 34. The filter 112 may first be inserted so that the lip 186 rests on a shelf of the
20 pop-up stem 34. Then, the spray head 35 may be rotated in such a manner that the female
21 threads within the inlet portion 114 of the housing 106 engage the male threads of the
22 pop-up stem 34.

23 In operation, water flows through the pop-up stem 34 and through the mesh 190
24 of the filter 112 to reach the tapered bore 188. The water passes through the space

1 between the tapered bore 188 and the head 180 of the adjustment screw 110 to reach the
2 inlet portion 114 of the housing 106. The water then passes through the portion of the
3 outlet apertures 132, 134, 136, 138, 140, 142 that is not blocked by the cam 108 and
4 impinges against the conical portion 154 of the deflector 104. The water is deflected
5 outward by the slope of the conical portion 154 so that the water is sprayed outward and
6 upward from the spray head 35.

7 The flow rate of the water sprayed from the spray head 35 may be limited by the
8 size of the gap between the head 180 of the adjustment screw 110 and the tapered bore
9 188. A screwdriver or other tool may be used to engage the slot 184 to rotate the
10 adjustment screw 110, thereby moving the head 180 toward or away from the tapered
11 bore 188. The head 180 may be moved to abut the tapered bore 188 to cut off water flow
12 to the spray head 35. Alternatively, the head 180 may be moved far enough from the
13 tapered bore 188 that the flow rate of water through the spray head 35 is limited primarily
14 by the exposed flow area of the outlet apertures 132, 134, 136, 138, 140, 142.

15 As described previously, the relative orientations of the plate 124 and the cam 108
16 determine the angle through which water exits the spray head 35. A user may rotate the
17 adjustment dial 100 by hand to rotate the cam 108 to the desired orientation with respect
18 to the housing 106. The cam 108 rotates about the cam axis 120, but does not move
19 along it. Accordingly, the cam 108 rotates "in-plane," or without moving from a
20 stationary plane. The manner in which the cam 108 determines the spray pattern will be
21 further illustrated and described in connection with Figures 3A, 3B, and 3C, as follows.

22 Referring to Figure 3A, a plan view illustrates the housing 106 and the cam 108 in
23 isolation. The housing 106 and the cam 108 (shown in phantom lines) are relatively
24 positioned to provide quarter-circle (*i.e.*, 90°) watering. As illustrated, the first outlet

1 aperture 132 has a radius 192 with respect to the cam axis 120. The radius 192 gradually
2 increases along the length of the first outlet aperture 132.

3 Each of the outlet apertures 132, 134, 136, 138, 140, 142 extends through an
4 angle of approximately 60°. The outlet apertures 132, 134, 136, 138, 140, 142,
5 collectively, extend substantially full-circle, or through an angle of 360°, within which the
6 radius 192 of the outlet apertures 132, 134, 136, 138, 140, 142, collectively, increases
7 gradually. Thus, as mentioned previously, the outlet apertures 132, 134, 136, 138, 140,
8 142 form a spiral shape with respect to the cam axis 120, which may accordingly be
9 referred to as a “slot axis” of the outlet apertures 132, 134, 136, 138, 140, 142.

10 In alternative embodiments, the outlet aperture(s) need not extend full-circle, but
11 may extend through an angle of less than 360°. The corresponding cam need not have a
12 full-circle spiral shape, but may instead have an edge that is spiral shaped through an
13 angle of the same magnitude as the angle through which the outlet aperture(s) extend. A
14 “spiral” shape need not extend full-circle, but must simply have a gradually increasing
15 radius through an angle.

16 As shown, the cam 108 is oriented such that the flat edge 164 of the cam 108
17 substantially bisects the fifth outlet aperture 140. Accordingly, the entire sixth outlet
18 aperture 142 and half of the fifth outlet aperture 140 are uncovered by the cam 108 and
19 available to conduct water 22 flow out of the housing 106. The first, second, third, and
20 fourth outlet apertures 132, 134, 136, 138, and half of the fifth outlet aperture 140, are
21 blocked by the cam 108. The resulting spray pattern is an angular portion of a circle, or
22 an arc 194 of 90°.

23 Referring to Figure 3B, a plan view again illustrates the housing 106 and the cam
24 108 in isolation. In Figure 3B, the cam 108 (shown in phantom lines) is oriented such

1 that the flat edge 164 extends substantially between the third and fourth outlet apertures
2 136, 138. Consequently, the first, second and third outlet apertures 132, 134, 136 are
3 blocked by the cam 108, and the fourth, fifth, and sixth outlet apertures 138, 140, 142 are
4 unblocked to conduct water 22 out of the housing 106. The resulting spray pattern is
5 half-circle, or an arc 195 of 180°.

6 Referring to Figure 3C, a plan view again illustrates the housing 106 and the cam
7 108 in isolation. In Figure 3C, the cam 108 (shown in phantom lines) is oriented such
8 that the flat edge 164 extends substantially between the first and sixth outlet apertures
9 132, 142. Consequently, all of the outlet apertures 132, 134, 136, 138, 140, 142 are
10 substantially unblocked to conduct water 22 out of the housing 106. The resulting spray
11 pattern is full-circle, or an arc 196 of 360°.

12 Notably, the spray head 35 may have a minimum spray angle, such as about 20°.
13 Accordingly, the spray head 35 may not be able to spray water through an angle under
14 about 20°. Thus, although the spray head 35 is adjustable to provide substantially full-
15 circle spray, this does not imply that there is no minimum spray angle.

16 Referring to Figure 4, an exploded, perspective view illustrates a spray head 198
17 according to one alternative embodiment of the invention. The spray head 198 has an
18 adjustment dial 100, a shaft 102, a cam 108, and an adjustment screw 110 that may be
19 substantially identical to those of the previous embodiment. The spray head 198 may be
20 used in conjunction with a filter 112, like that illustrated in Figure 2. Additionally, the
21 spray head 198 has a deflector 204 and a housing 206, which may be different from those
22 of the previous embodiment in a number of respects.

23 More precisely, the housing 206 may have an inlet portion 114 like that of the
24 previous embodiment, and an outlet portion 216. The housing 206 has an outer wall 118

1 with a tubular shape coaxial with a cam axis 120. The outer wall 118 transcends the inlet
2 and outlet portions 114, 216, with indentations 122 to facilitate manual threaded
3 assembly. A plate 224 spans the outer wall 118 within the outlet portion 216. The plate
4 has a central hole 126 with a lip 128 like that of the previous embodiment. The plate 224
5 also has first, second, third, fourth, fifth, and sixth outlet apertures 132, 134, 136, 138,
6 140, 142 that are separated by bridges 144 like those of the previous embodiment.
7 However, in the spray head 198, no receiving hole 130 need be formed in the plate 224.

8 The deflector 204 has a lip 150 like that of the previous embodiment and a central
9 hole 252 extending along the cam axis 120. The central hole 252 may be slightly larger
10 in diameter than the central hole 152 of the deflector 108 of the previous embodiment to
11 facilitate rotation of the deflector 204 around the shaft 102. The deflector 204 also has a
12 conical portion 254 that is truncated along a plane perpendicular to the cam axis 120. A
13 plurality of vanes 256 is formed in the resulting circular surface. The vanes 256 operate
14 to induce rotation of the deflector 204 in response to impingement of water exiting the
15 housing 206 against the deflector 204. The vanes 256 will be illustrated with greater
16 detail in Figure 5.

17 Referring to Figure 5, a bottom view illustrates the deflector 204 of Figure 4 in
18 isolation. As shown, the vanes 256 extend outward with a counterclockwise curvature,
19 with reference to the bottom view of Figure 5. The deflector 204 also has a hub 258,
20 which may have a generally annular configuration similar to that of the previous
21 embodiment. The hub 258 is insertable into the central hole 126 of the plate 224 in such
22 a manner that the hub 258 rests on the lip 128. The hub 258 may have an outside
23 diameter selected such that the hub 258 is relatively freely rotatable within the central
24 hole 126.

1 As shown, the vanes 256 are separated from each other by grooves 259 that
2 extend outward from the hub 258 with a counterclockwise curvature like that of the vanes
3 256. The water impinges against the vanes 258 and flows into the grooves 259. The
4 water then flows outward along the grooves 259. As the water flows along the grooves
5 259, the water presses against the sides of the vanes 256 to induce rotation of the
6 deflector 204 along the clockwise direction with respect to the view of Figure 5, or along
7 the counterclockwise direction as viewed from above. Accordingly, the water leaves the
8 deflector 204 with velocity including a tangential component as well as a radial
9 component. The water may thus be more uniformly distributed to the surrounding soil,
10 and the spray head 198 may produce a swirling pattern that is comparatively attractive in
11 operation.

12 Referring again to Figure 4, the spray head 198 provides a variable spray arc in a
13 manner similar to that of the previous embodiment. More precisely, the orientation of the
14 cam 108 with respect to the outlet apertures 132, 134, 136, 138, 140, 142 determines the
15 angle through which water is sprayed from the spray head 198. Accordingly, a user may
16 establish the spray pattern and the flow rate of water distributed by the spray head 198 by
17 rotating the adjustment dial 100 and the adjustment screw 110, as described in connection
18 with the previous embodiment.

19 The various components of the spray head 198 may be manufactured in a manner
20 similar to that of the previous embodiment. As above, operations such as stamping,
21 injection molding, and the like may be used.

22 Furthermore, the spray head 198 is assembled in a manner similar to that of the
23 spray head 35 of the previous embodiment. The deflector 204 may first be inserted into
24 engagement with the housing 206 by inserting the hub 258 into the central hole 126 of the

1 plate 224 of the housing 206 in such a manner that the hub 258 is able to rotate within the
2 central hole 126 to permit relative rotation between the deflector 204 and the housing
3 206. The adjustment dial 100 and the cam 108 are press fit onto the first and second ends
4 174, 176, respectively, of the shaft 102 in such a manner that the shaft 102 extends
5 through the central holes 124, 252 of the housing 206 and the deflector 204. The
6 adjustment screw 110 is threaded into engagement with the bore 178 of the shaft 102.

7 In other embodiments, spray heads according to the invention may be used to
8 irrigate in patterns that are not bounded by circular shapes. For example, spray heads
9 according to the present invention may be used to irrigate narrow strips of land, such as
10 the strip commonly positioned between a sidewalk and a street. A strip head according to
11 one exemplary embodiment of the invention will be shown and described in connection
12 with Figures 6 and 7.

13 Referring to Figure 6, an exploded, perspective view illustrates a spray head 298
14 according to another alternative embodiment of the invention. The spray head 298 is
15 designed to distribute water over an area bounded by a narrow rectangular shape, such as
16 a strip as described above. As shown, the spray head 298 includes an adjustment dial
17 100, a shaft 102, and an adjustment screw 110. The spray head 198 may be used in
18 conjunction with a filter 112, like that illustrated in Figures 2 and 4. The spray head 298
19 also has a deflector 304, a housing 306, and a cam 308 that are somewhat different from
20 those described previously.

21 As shown, the housing 306 has an inlet portion 114 like those described
22 previously and an outlet portion 316. The housing 306 has an outer wall 118 with a
23 tubular shape coaxial with a cam axis 120. The outer wall 118 transcends the inlet and
24 outlet portions 114, 316 and has indentations 122 to facilitate manual rotation for

1 threaded engagement. The outlet portion 316 has a plate 324 that extends across the
2 outer wall 118, substantially perpendicular to a cam axis 120.

3 The plate 324 has a central hole 126 with a lip 128 like those of the previous
4 embodiments. The plate 324 also has a receiving hole 130 like that of the plate 124 of
5 the spray head 35 of the first embodiment. Additionally the plate 324 has a first outlet
6 aperture 332, a second outlet aperture 334, and a third outlet aperture 336 that are
7 arranged around the central hole 126. Each of the first and second outlet apertures 332,
8 334 may comprise a generally circular shape disposed near the outer wall 118. The third
9 outlet aperture 336 may comprise an elongated slot that extends radially. Thus, one end
10 of the third outlet aperture 336 is disposed near the outer wall 118, like the first and
11 second outlet apertures 332, 334, and the other end of the third outlet aperture 336 is
12 disposed near the central hole 126.

13 As shown, the deflector 304 has a lip 150 like those of the previous
14 embodiments. The deflector 304 also has a central hole 152 like that of the deflector 104
15 of the first embodiment. A detent mechanism 346 extends from the deflector 304 toward
16 the adjustment dial 100. The detent mechanism 346 has a ball 348 seated within a hole
17 formed in the deflector 304. The ball 348 is urged away from the deflector 304 by a
18 spring disposed within the hole. The adjustment dial 100 has corresponding divots or
19 ridges that are engaged by the ball 348. The engagement of the ball 348 with the
20 adjustment dial 100 tends to keep the adjustment dial 100 in one of a number of discrete
21 positions with respect to the deflector 304. These relative positions correspond to
22 different spray patterns that the spray head 298 may be set to provide via rotation of the
23 adjustment dial 100 to a corresponding orientation.

1 Detent mechanisms like the detent mechanism 346 may be used in conjunction
2 with the first embodiment, if desired. For example, such a detent mechanism may be
3 used to cause the spray head 35 to “snap” between commonly used angles such as 30°,
4 45°, 60°, 90°, 180°, 270°, and 360°.

5 Returning to the embodiment of Figure 6, the deflector 304 also has a conical
6 portion 354 that extends from the lip 150 toward the housing 306. An orientation post
7 355 and a hub 258 like that of the previous embodiment extend toward the housing 306
8 from the conical portion 354. The orientation post 355 may be inserted into the receiving
9 hole 130 and the hub 258 may be inserted into the central hole 126 of the plate 324 in
10 such a manner that the deflector 304 is unable to rotate with respect to the housing 306.

11 The conical portion 354 may be uniquely shaped to distribute water along
12 multiple patterns. For example, the conical portion 354 may have a first water
13 distribution feature 356, a second water distribution feature 357, and a third water
14 distribution feature 358. The first water distribution feature 356 and the third water
15 distribution feature 358 may be disposed on opposite sides of the conical portion 354, and
16 the second water distribution feature 357 may be displaced from each of the first and
17 third water distribution features 356, 358 by 90°, for example.

18 As shown, each of the first, second, and third water distribution features 356, 357,
19 358 takes the form of a trough formed in the surface of the conical portion 354. The first,
20 second, and third water distribution features 356, 357, 358 may each be shaped to spray
21 water along a substantially consistent pattern. A “water distribution feature” is a feature
22 capable of receiving a water flow and ejecting the water through the air along a desired
23 pattern. In alternative embodiments of the invention, water distribution features may

1 comprise enclosed passageways, elements that protrude into the water stream to control
2 the flow, shaped apertures, and/or other known fluid conduction and control features.

3 The first and third water distribution features 356, 358 may each be designed to
4 provide end strip irrigation so that the first and third water distribution features 356, 358
5 may be used together to provide center strip irrigation. The second water distribution
6 feature 357 may be designed to provide side strip irrigation.

7 Accordingly, the first, second, and third water distribution features 356, 357, 358
8 are aligned with the first, second, and third outlet apertures 332, 334, 336, respectively,
9 along the transverse direction 16. These types of irrigation provided by the first, second,
10 and third water distribution features 356, 357, 358 will be shown and described in greater
11 detail in connection with Figures 7B, 7D, and 7F.

12 The cam 308 has an outer edge 360 with a generally circular shape. The cam 308
13 also has a central hole 162 like those of the previous embodiments. A notch 364 is
14 formed in the outer edge 360. Additionally, a hole 366 is formed in the cam 308, on the
15 side of the cam 308 opposite from the notch 364. The hole 366 is positioned with a
16 displacement from the central hole 162 smaller than the displacement of the notch 364
17 from the central hole 162. The notch 364 and the hole 366 provide open portions of the
18 cam 308, through which water is able to flow beyond the cam 308.

19 The adjustment dial 100, shaft 102, deflector 304, housing 306, cam 308, and
20 adjustment screw 110 may be formed via methods similar to those described above, in
21 connection with the spray head 35. For example, the adjustment dial 100 and the cam
22 308 may be stamped from relatively thin strips of metal, the shaft 102 may be cut from a
23 length of threaded tubular stock, and the deflector 304 and housing 306 may be injection
24 molded. The adjustment screw 110 may be formed via known methods such as casting.

1 The adjustment dial 100, shaft 102, deflector 304, housing 306, cam 308, and
2 adjustment screw 110 may be assembled in a manner similar to that of the previous
3 embodiments. More precisely, the deflector 304 and the housing 306 may first be aligned
4 and moved together in such a manner that the orientation post 355 is inserted into the
5 receiving hole 130 and the hub 258 is inserted into the central hole 126 of the plate 324.
6 The orientation post 355 and the hub 258 may be attached within the receiving hole 130
7 and the central hole 126, respectively, via press fitting, adhesive bonding, or the like to
8 prevent disassembly or relative rotation of the deflector 304 and the housing 306.

9 The adjustment dial 100 and the cam 308 may then be pressed into engagement
10 with the shaft 102 in such a manner that the first end 174 of the shaft 102 is press fit into
11 the central hole 172 of the adjustment dial 100 and the second end 176 of the shaft 102 is
12 press fit into the central hole 162 of the cam 308. The shaft 102 then
13 extends through the central holes 126, 152 of the plate 324 and the deflector 304 so that
14 the adjustment dial 100 is disposed adjacent to the deflector 304 and the cam 308 is
15 disposed adjacent to the plate 324. The adjustment screw 110 may then be threaded into
16 the bore 178 of the shaft 102 in such a manner that the head 180 protrudes from the bore
17 178 proximate the second end 176 of the shaft 102 and the slot 184 is accessible through
18 the first end 174.

19 The spray head 298 is then fully assembled. The filter 112 and the spray head
20 298 may then be attached to the corresponding pop-up stem 34 in the manner described
21 above, in connection with the spray head 35 of Figures 1-3.

22 In operation, water flows into the spray head 298 through the filter 112.
23 Adjustment of the flow rate of water entering the spray head 298 is provided by altering
24 the position of the head 108 of the adjustment screw 110 relative to the tapered bore 188

1 of the filter 112, as described above. The water flows against the cam 308, and flows
2 through any of the outlet apertures 332, 334, 336 that are exposed through the notch 364
3 or the hole 366 of the cam 308. The orientation of the cam 308 with respect to the plate
4 324 determines which of the outlet apertures 332, 334, 336 are exposed to receive water
5 flow.

6 After moving through the exposed outlet aperture(s) 332, 334, and/or 336, the
7 water impinges against the corresponding one or more of the first, second, and third water
8 distribution features 356, 357, 358. The water is distributed by the corresponding one or
9 more of the water distribution features 356, 357, 358 along a pattern corresponding to the
10 shape of the water distribution feature(s) 356, 357, and/or 358 that receive the water. The
11 manner in which water is distributed will be shown and described with greater detail in
12 connection with Figures 7A-7F, as follows.

13 Referring to Figure 7A, a plan view illustrates the housing 306 and the cam 308
14 (shown in phantom lines) of the spray head 298 of Figure 6. The cam 308 is shown
15 oriented for center strip irrigation. More precisely, the cam 308 is oriented such that the
16 notch 364 is aligned with the first outlet aperture 332 and the hole 366 is aligned with an
17 inwardly disposed portion of the third outlet aperture 336. Accordingly, water flows
18 through the first and third outlet apertures 332, 336 to impinge against the first and third
19 water distribution features 356, 358, respectively. The first and third water distribution
20 features 356, 358 cooperate to provide water flow from the spray head 298 through 360°
21 for center strip irrigation.

22 Referring to Figure 7B, a plan view illustrates a strip area 392 in which the spray
23 head 298 of Figure 6 is installed, with the cam 308 and housing 306 relatively positioned
24 as shown in Figure 7A. The strip area 392 may be a section of a strip disposed between a

1 sidewalk and a street, and may thus have a rectangular shape 394 having two long sides
2 395 and two short sides 396. The long sides 395 may each be from about twenty to about
3 forty feet in length, and the short sides may each be from about two to about five feet in
4 length.

5 The spray head 298 is installed in the center of the strip area 392. The first water
6 distribution feature 356 faces toward one of the short sides 396, and the third water
7 distribution feature 358 faces in the opposite direction, toward the opposite short side
8 396. Each of the first and third water distribution features 356, 358 distributes water over
9 about a 180° arc along a generally rectangular pattern so that each of the first and third
10 water distribution features 356, 358 irrigates half of the strip area 392. Accordingly, the
11 first and third water distribution features 356, 358 cooperate to irrigate substantially the
12 entire strip area 392. Thus, the spray head 298 provides a rectangular spray pattern, or
13 spray that is generally limited to the area within a narrow rectangle. A “spray pattern” is
14 the shape of the area irrigated by a sprinkler head, as viewed from overhead.

15 Referring to figure 7C, a plan view illustrates the housing 306 and the cam 308 of
16 the spray head 298 of Figure 6. The cam 308 is shown oriented for side strip irrigation.
17 More precisely, the cam 308 is oriented such that the notch 364 is aligned with the
18 second outlet aperture 334, and the hole 366 is not aligned with any of the outlet apertures
19 332, 334, 336. Accordingly, water flows through the second outlet apertures 334 to
20 impinge against the second water distribution features 357. The second water
21 distribution feature 357 provides water flow from the spray head 298 through 180° for
22 side strip irrigation.

23 Referring to Figure 7D, a plan view illustrates a strip area 392 in which the spray
24 head 298 of Figure 6 is installed, with the cam 308 and housing 306 relatively positioned

1 as shown in Figure 7C. As in Figure 7B, the strip area 392 may be a section of a strip
2 disposed between a sidewalk and a street, with a rectangular shape 394 having two long
3 sides 395 and two short sides 396.

4 The spray head 298 is installed on a side of the strip area 392, proximate the
5 center of one of the long sides 395 of the rectangular shape 394. The second water
6 distribution feature 357 faces toward the center of the strip area 392. The second water
7 distribution feature 357 distributes water over about a 180° arc along a generally
8 rectangular pattern so that the second water distribution feature 357 irrigates substantially
9 the entire strip area 392.

10 Referring to figure 7E, a plan view illustrates the housing 306 and the cam 308
11 (shown in phantom lines) of the spray head 298 of Figure 6. The cam 308 is shown
12 oriented for end strip irrigation. More precisely, the cam 308 is oriented such that the
13 notch 364 is aligned with the outward portion of the third outlet aperture 336 and the hole
14 366 is not aligned with any of the outlet apertures 332, 334, 336. Accordingly, water
15 flows through the third outlet aperture 336 to impinge against the third water distribution
16 features 358. The third water distribution feature 358 provides water flow from the spray
17 head 298 through 180° for end strip irrigation.

18 Referring to Figure 7F, a plan view illustrates a strip area 392 in which the spray
19 head 298 of Figure 6 is installed, with the cam 308 and housing 306 relatively positioned
20 as shown in Figure 7E. As in Figure 7B, the strip area 392 may be a section of a strip
21 disposed between a sidewalk and a street, with a rectangular shape 394 having two long
22 sides 395 and two short sides 396.

23 The spray head 298 is installed on a side of the strip area 392, proximate the
24 center of one of the short sides 396 of the rectangular shape 394. The third water

1 distribution feature 358 faces toward the center of the strip area 392. The third water
2 distribution feature 357 distributes water over about a 180° arc along a generally
3 rectangular pattern so that the second water distribution feature 357 irrigates about half of
4 the strip area 392.

5 According to alternative configurations, other watering patterns may be used in
6 place of or in addition to those provided by the spray head 298. For example, quarter-
7 circle, half-circle, and/or full-circle spray patterns may be used. Additional outlet
8 apertures (not shown) may be used in conjunction with additional holes and/or notches in
9 a cam to provide a wider array of spray patterns.

10 The present invention may be embodied in other specific forms without departing
11 from its structures, methods, or other essential characteristics as broadly described herein
12 and claimed hereinafter. The described embodiments are to be considered in all respects
13 only as illustrative, and not restrictive. The scope of the invention is, therefore, indicated
14 by the appended claims, rather than by the foregoing description. All changes that come
15 within the meaning and range of equivalency of the claims are to be embraced within
16 their scope.